

# > NINPC-TX

EVAC ELEVATOR AUDIO, CAMERA AND DISPLAY




## SECURITY

### EVAC 2-WAY COMMUNICATION

This product provides an in-car interface which communicates with both the Machine Room Station and the Security Command Station over the existing network. Includes a ceiling mount camera and a 2.7 OLED display for text data. Optional upgrade to an Elite P.I. product for text data.

#### FEATURES:

- > Audio and Visual text communications
- > 24-30 VDC supply from car
- > Single twisted shielded pair required in traveler
- > Battery backup provided
- > Covert ceiling mount camera



**C.E. Electronics, Inc.**

2107 Industrial Drive | Bryan, Ohio 43506 | Ph: (419) 636-6705 | Fx: (419) 636.2516 | [www.cееlectronics.com](http://www.cееlectronics.com)




C.E. Electronics, Inc.  
2107 Industrial Drive  
Bryan, OH 43506  
PH (419) 636-6705 FX (419) 636-2516  
www.ceelectronics.com

# EVAC SYSTEM

Ver. 2 Rel. 7/21/2026

LINE  
DIAGRAM

EVAC  
2-WAY  
COMMUNICATION






C.E. Electronics, Inc.  
2107 Industrial Drive  
Bryan, OH 43506  
PH (419) 636-6705 FX (419) 636-2516  
www.ceelectronics.com



# NINPC-TX

Ver. 5 Rel. 1/5/2026

EVAC  
2-WAY  
COMMUNICATION




- OR -




DETAIL "A"  
Ø1/8 (.125) HOLE

DETAIL "B"  
#4-40 x 1/2 STUD  
2 PLACES

MICROPHONE ASSEMBLY  
CE # 9MICASSY00  
CUT OUT AND STUD  
PANEL PREP DETAIL



NINT-C  
NETWORK CARD  
INTERFACE BOARD



## EVAC ELEVATOR AUDIO, CAMERA and DISPLAY

This product provides an in-car interface which communicates with both the Machine Room Station and the Security Command Station over the existing network. Includes a ceiling mount camera and a 2.7 OLED display for text data. Optional interface to an Elite P.I. product for text data.

### Features:

- \* Audio and Visual text communications
- \* 24-30 VDC supply from car
- \* Single twisted shielded pair required in traveler
- \* Battery backup provided
- \* Covert ceiling mount camera

### To Order - NINPC-TX


"F" = Flush; 2.7 OLED Display  
"R" = Remote (\*) see note  
"S" = Surface Mount (SS#4); 2.7 OLED Display  
"X" = No Display/Interface cable to Elite PI

\* Remote option works with any Mini PI, Standard PI or Elite Pro PI

Note: Speaker assembly; CE # 9SPKRASY03 mounting distance  
MINIMUM 12 inches from microphone assembly; CE # 9MICASSY00



# EVAC 2-WAY COP





OPTIONAL ELITE PI INTERFACE

CAMERA



OELD (standard)



## ELITE PI POSITION INDICATOR (PI)

### PI NORMAL OPERATION:

Screen will display at minimum Direction Arrow and Floor Position.

### 2-WAY EMERGENCY CALL OPERATION, CAPABLE:

(Requires additional battery backup)

Display will change to text display "Two-Way Communication Calling for Help"

Security will answer and attempt to establish voice communication first.


If voice can't be established, security then has a choice of five standard text messages or can type message with the on screen touch keyboard.

Five Standard One Touch Texts: 1) Are You OK? 2) Do you need help? 3) Can you hear me? 4) Help is on the way. 5) Help is On-Site.

Security station screen will show Car video feed for the duration of emergency call.




Normal Operation PI



Emergency Call Display

Emergency Call is initiated by pressing the Emergency Phone Button.

Occupant presses applicable Door Open or Door Closed to answer security questions if COP doesn't have yes/no buttons.



**C.E. Electronics, Inc.**  
elevate yourself to new heights



Industrial Drive  
Bryan, OH 43506



call us:  
419.636.6705



web:  
[www.ceelectronics.com](http://www.ceelectronics.com)